

PNEUMATICALLY ACTUATED GLOBE VALVE

IBR CERTIFIED GLOBE VALVE

IPC Make Flameproof
Limit Switch Box with
Position Indicator



SIZE
(12")
300 MM

CERTIFICATION
IBR

PRESSURE RATING
#150

TESTING STD.
**BS EN
12266-1**

VALVE MAKE & SERIES IPC - 813	CONSTRUCTION OS & Y TYPE BOLTED BONNET	TYPE GLOBE VALVE	DESIGN STD BS 1873
FACE TO FACE ASME B 16.10	END CONNECTION ASME B16.5, FE, RF	PAINT HEAT RESISTANT ALUMINIM	OPERATING TEMP AS PER ASME B16.34
OPERATING PRESSURE 20 Kg/cm² Max	LEAKAGE CLASS BS EN 12266-1, RATE - D	FLOW DIRECTION UNI- DIRECTIONAL	TRIM NO. SS316L-(TR-52)
BODY MOC ASTM A 216 GR. WCB	PLUG MOC ASTM A351 GR. CF3M	STEM MOC ASTM A276 TP 316L	SEAT MOC ASTM A182 GR. F316L
ACTUATOR TYPE PISTON TYPE PNEUMATIC ACTUATOR	FUNCTION (DUTY) ON-OFF	SERVICE STEAM	AIR FAIL POSITION CLOSE