

ELECTRICALLY ACTUATED GLOBE VALVE

- IBR Certified Globe Valve
- Bypass arrangement to reduce pressure as well as operating torque



SIZE (16") 400 MM	PRESSURE RATING CLASS 300	TESTING STD. API 598	VALVE SERIES IPC GLOBE VALVE – 813
----------------------	------------------------------	-------------------------	--

CONSTRUCTION BOLTED BONNET	DESIGN STD BS 1873 / ASME B16.34	END CONNECTION ASME B 16.5, FERF	FACE TO FACE ASME B 16.10
TRIM NO. TRIM 8	OPERATION ELECTRIC ACTUATOR WITH GEAR BOX	FLOW DIRECTION UNI- DIRECTIONAL	SPECIAL BYPASS GLOBE VALVE WITH ELECTRICAL ACTUATOR
BODY MOC ASTM A216 Gr. WCB	PLUG MOC ASTM A216 Gr. WCB + 13%Cr	SEAT MOC ASTM A156 Gr.70 + ST6	STEM MOC ASTM A276 TP 410
POWER SUPPLY 415 V, 50HZ, 3 PHASE	FUNCTION (DUTY) ON-OFF	POWER SUPPLY FAIL POSITION Fail lock (Stay put)	PAINT HEAT RESISTANT ALUMINIM