

Y TYPE FLUSH TANK BOTTOM VALVE



<p>SIZE DN 300 x DN 250</p>	<p>END CONNECTIONS FLANGED END</p>	<p>PRESSURE RATING CLASS 150</p>	<p>VALVE ACTION TIME LESS THAN 5 SECONDS</p>
<p>VALVE MAKE & SERIES IPC 551 SERIES, Y TYPE FLUSH TANK BOTTOM VALVE</p>	<p>CONSTRUCTION Y TYPE FLUSH DISC RISING IN TANK</p>	<p>SOLENOID VALVE 3/2 WAY FLAMEPROOF SOLENOID 24VDC</p>	<p>LIMIT SWITCH BOX FLAME PROOF WITH TWO PROXIMITY SENSORS</p>
<p>ACTUATOR MODEL IPC 300T MULTI SPRING DIAPHRAM ACTUATOR</p>	<p>OPERATION PNEUMATIC DIAPHARGM TYPE SPRING RETURN ACTUATOR</p>	<p>AIR SUPPLY 3.5 KG/CM2(G)</p>	<p>FLOW DIRECTION UNI-DIRECTIONAL</p>
<p>BODY MOC ASTM A351 Gr. CF3M</p>	<p>PLUG MOC SS316L + PEEK ENCAPS</p>	<p>SEAT MOC SS316L</p>	<p>STEM MOC SS316L</p>